

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

### Servolenkungsoel-Verlust Stop

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Additives

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)

H412-Harmful to aquatic life with long lasting effects.

P273-Avoid release to the environment.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH208-Contains 1,3,4-thiadiazole-2(3H)-thione, 5-(tert-dodecyldithio)-. May produce an allergic reaction.

#### 2.3 Other hazards

Page 2 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 Product can compose a film on the water surface, which can prevent oxygen exchange.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based</b>	
Registration number (REACH)	01-2119474889-13-XXXX
Index	649-483-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	276-738-4
CAS	72623-87-1
content %	20-<40
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304
<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b>	
Registration number (REACH)	01-2119480132-48-XXXX
Index	649-469-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	265-159-2
CAS	64742-56-9
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304
<b>Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich</b>	
Registration number (REACH)	01-2119969520-35-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	800-172-4
CAS	398141-87-2
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Chronic 2, H411
<b>Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate</b>	
Registration number (REACH)	01-0000015551-76-XXXX
Index	607-530-00-7
EINECS, ELINCS, NLP, REACH-IT List-No.	406-040-9
CAS	125643-61-0
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Chronic 4, H413
<b>Short-, medium- and long-chain alkyl methacrylates and short-chain alkyl methacrylamide copolymer (EU ACC-QT664993-91/ GB ACN-AFT-25032021-PXL-01)</b>	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	---
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Irrit. 2, H319
<b>2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol</b>	
Registration number (REACH)	01-2119510877-33-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	620-540-6
CAS	1218787-32-6

Page 3 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)

<b>1,3,4-thiadiazole-2(3H)-thione, 5-(tert-dodecyldithio)-</b>	
<b>Registration number (REACH)</b>	01-2120761104-64-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	813-543-0
<b>CAS</b>	73984-93-7
<b>content %</b>	0,01-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Sens. 1B, H317 Aquatic Chronic 3, H412

<b>3-((C9-11-iso, C10-rich)alkyloxy)propan-1-amine</b>	
<b>Registration number (REACH)</b>	01-2119974116-35-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	939-485-7
<b>CAS</b>	218141-16-3
<b>content %</b>	0,01-<0,25
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=1)

<b>Methyl-1H-benzotriazole</b>	
<b>Registration number (REACH)</b>	01-2119979081-35-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	249-596-6
<b>CAS</b>	29385-43-1
<b>content %</b>	0,01-<0,25
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Repr. 2, H361d Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Page 4 of 21  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 27.04.2021 / 0015  
Replacing version dated / version: 13.11.2019 / 0014  
Valid from: 27.04.2021  
PDF print date: 28.04.2021  
Servolenkungsoel-Verlust Stop

Danger of aspiration.

#### **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Drying of the skin.

Irritation of the skin.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

##### **Suitable extinguishing media**

CO<sub>2</sub>

Foam

Dry extinguisher

Water jet spray

##### **Unsuitable extinguishing media**

High volume water jet

#### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Oxides of phosphorus

Toxic gases

Flammable vapour/air mixtures

#### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

### **SECTION 6: Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure good ventilation.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### **6.2 Environmental precautions**

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

#### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### **7.1 Precautions for safe handling**

##### **7.1.1 General recommendations**

Ensure good ventilation.

Avoid contact with eyes or skin.

Page 5 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

Do not carry cleaning cloths soaked in product in trouser pockets.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Store in a dry place.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures: - Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---		Other information: ---

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - oral		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3	8h

Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	0,37	mg/kg	
	Environment - sediment, marine		PNEC	0,037	mg/kg	
	Environment - soil		PNEC	189	mg/kg	
	Environment - freshwater		PNEC	0,0043	mg/kg	
	Environment - marine		PNEC	0,00043	mg/kg	
Consumer	Human - inhalation		DNEL	0,74	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	4,3	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,43	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,6	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	3	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	1	mg/cm2	

Page 6 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

Workers / employees	Human - dermal	Long term, local effects	DNEL	0,006	mg/cm2	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	20	mg/kg	

<b>Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	2,4	µg/l	
	Environment - marine		PNEC	0,33	µg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	24	µg/l	

<b>2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,21	µg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,21	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,21	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,3	mg/kg bw/d	

<b>1,3,4-thiadiazole-2(3H)-thione, 5-(tert-dodecyldithio)-</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,04	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,42	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,42	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,83	mg/kg bw/day	

<b>3-((C9-11-iso, C10-rich)alkyloxy)propan-1-amine</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,84	µg/l	
	Environment - marine		PNEC	0,084	µg/l	
	Environment - sediment, freshwater		PNEC	3,19	mg/kg dw	
	Environment - sediment, marine		PNEC	0,32	mg/kg dw	
	Environment - soil		PNEC	1,59	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1,3	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,827	µg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,74	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,25	mg/kg bw/day	

Page 7 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,9	mg/m <sup>3</sup>	
---------------------	--------------------	-----------------------------	------	-----	-------------------	--

Methyl-1H-benzotriazole						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,008	mg/l	
	Environment - marine		PNEC	0,008	mg/l	
	Environment - sediment, freshwater		PNEC	0,0025	mg/kg	
	Environment - sediment, marine		PNEC	0,0025	mg/kg	
	Environment - soil		PNEC	0,0024	mg/kg	
	Environment - sewage treatment plant		PNEC	39,4	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,086	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,25	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,25	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	4,4	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	8,8	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,5	mg/kg	

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg	

06 WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".



Page 8 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:  
 Protective nitrile gloves (EN 374).  
 Permeation time (penetration time) in minutes:  
 > 480  
 Minimum layer thickness in mm:  
 0,4  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 If OES or MEL is exceeded.  
 Filter A P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

# SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>100 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,888 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined



Page 9 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	166 mm <sup>2</sup> /s (40°C)
Viscosity:	26 mm <sup>2</sup> /s (100°C)
Explosive properties:	Not determined
Oxidising properties:	Not determined

## 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

### 10.4 Conditions to avoid

Protect from humidity.  
Open flame, ignition sources

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Servolenkungsoel-Verlust Stop						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						Based on available data, the classification criteria are not met., Classification based on toxicological analyses.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Page 10 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

Other information:						Classification according to calculation procedure.
--------------------	--	--	--	--	--	----------------------------------------------------

<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:					OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 412 (Subacute Inhalation Toxicity - 28-Day Study)	Negative
Aspiration hazard:						Asp. Tox. 1

**Distillates (petroleum), solvent-dewaxed light paraffinic**

Page 11 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Mist
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Guinea pig		No (skin contact)
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Mouse		Female, Negative
Reproductive toxicity:	NOAEL	>2000	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Reproductive toxicity:	NOAEL	>1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	
Aspiration hazard:						Yes
Symptoms:						drying of the skin., vomiting, nausea

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity:				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Symptoms:						headaches, dizziness, nausea, mental confusion, drowsiness, drowsiness

GB

Page 12 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	100	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	500	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	

**Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Rat		Negative, Analogous conclusion
Aspiration hazard:						Negative

**Short-, medium- and long-chain alkyl methacrylates and short-chain alkyl methacrylamide copolymer (EU ACC-QT664993-91/ GB ACN-AFT-25032021-PXL-01)**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	Analogous conclusion
Skin corrosion/irritation:				Rabbit		Not irritant, Analogous conclusion
Serious eye damage/irritation:		>75%		Rabbit		Eye Irrit. 2, Classification based on toxicological analyses.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion

**2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1500	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1C

Page 13 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion

<b>1,3,4-thiadiazole-2(3H)-thione, 5-(tert-dodecylidithio)-</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	200	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	Analogous conclusion

<b>3-((C9-11-iso, C10-rich)alkyloxy)propan-1-amine</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	300-2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	Female
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1B
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative

<b>Methyl-1H-benzotriazole</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	720	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant

Page 14 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):	LOAEL	30	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Positive
Reproductive toxicity (Effects on fertility):				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	150	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

### Servolenkungsoel-Verlust Stop

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Mechanical precipitation possible.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	>=100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	> 100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

Page 15 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

12.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	46	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.3. Bioaccumulative potential:	Log Kow		>6				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	NOEC/NOEL	10min	>1,93	mg/l		DIN 38412 T.8	

**Distillates (petroleum), solvent-dewaxed light paraffinic**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	LL50	48h	>1000	mg/l	Gammarus sp.	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Inherent
12.3. Bioaccumulative potential:	Log Pow		>3				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	4,6	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	63	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,313	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion



Page 16 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

12.2. Persistence and degradability:		28d	9,6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	BCF		27,54				measured
12.3. Bioaccumulative potential:	Log Kow		4,1			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	measured
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

**Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>74	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>3	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	4	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		9,2				Low
12.3. Bioaccumulative potential:	BCF	35d	260			OECD 305 (Bioconcentration - Flow-Through Fish Test)	Concentration in organisms possible.

**Short-, medium- and long-chain alkyl methacrylates and short-chain alkyl methacrylamide copolymer (EU ACC-QT664993-91/ GB ACN-AFT-25032021-PXL-01)**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l			Gobiocypris rarus
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriella subcapitata		Analogous conclusion
12.1. Toxicity to algae:	EC10	72h	76,6	mg/l	Pseudokirchneriella subcapitata		Maximum achievable concentration., Analogous conclusion

Page 17 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

12.1. Toxicity to daphnia:	EC10	21d	>100	mg/l	Daphnia magna		Analogous conclusion
12.2. Persistence and degradability:		28d	3,6	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable
Toxicity to bacteria:	EC50	3h	>1000	mg/l			

**2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	75	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		3,6				Low
12.1. Toxicity to fish:	LC50	96h	0,1	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	0,043	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC10	21d	0,0107	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	0,0538	mg/l	Pseudokirchneriella subcapitata	IUCLID Chem. Data Sheet (ESIS)	Analogous conclusion
12.2. Persistence and degradability:		28d	63	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable, Analogous conclusion calculated
12.3. Bioaccumulative potential:	BCF		110,2				
Toxicity to bacteria:	EC50	3h	167	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

**1,3,4-thiadiazole-2(3H)-thione, 5-(tert-dodecylthio)-**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		6,67				High
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EL50	48h	41	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EL50	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion

Page 18 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not readily biodegradable
Toxicity to bacteria:	EC50	16h	>8000	mg/l	Pseudomonas putida	DIN 38412 T.8	Analogous conclusion

3-((C9-11-iso, C10-rich)alkyloxy)propan-1-amine							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC50	3h	23,6	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.1. Toxicity to fish:	LC50	96h	2,14	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	21d	1,09	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC10	21d	0,738	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	0,082	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	68	%	activated sludge	OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable

Methyl-1H-benzotriazole							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	180	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to algae:	IC50	72h	75	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	8,58	mg/l		OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion Daphnia galeata
12.2. Persistence and degradability:		28d	4	%	activated sludge	Regulation (EC) 440/2008 C.4-D (DETERMINATION OF 'READY' BIODEGRAD. - MANOMETRIC RESPIROMETRY TEST)	Not readily biodegradable
12.1. Toxicity to daphnia:	EC10	21d	0,4	mg/l		OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion Daphnia galeata
Toxicity to bacteria:	EC50	24h	1060	mg/l	activated sludge	ISO 8192	Analogous conclusion

### SECTION 13: Disposal considerations

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsöl-Verlust Stop

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Uncontaminated packaging can be recycled.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

#### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 7,5 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 27.04.2021 / 0015  
 Replacing version dated / version: 13.11.2019 / 0014  
 Valid from: 27.04.2021  
 PDF print date: 28.04.2021  
 Servolenkungsoel-Verlust Stop

## SECTION 16: Other information

Revised sections: 1, 3, 8, 11, 12, 15  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.  
 H361d Suspected of damaging the unborn child.  
 H317 May cause an allergic skin reaction.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.  
 H413 May cause long lasting harmful effects to aquatic life.

Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Asp. Tox. — Aspiration hazard  
 Eye Irrit. — Eye irritation  
 Acute Tox. — Acute toxicity - oral  
 Skin Corr. — Skin corrosion  
 Eye Dam. — Serious eye damage  
 Aquatic Acute — Hazardous to the aquatic environment - acute  
 Skin Sens. — Skin sensitization  
 Repr. — Reproductive toxicity

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 ATE Acute Toxicity Estimate  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level

Page 21 of 21  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 27.04.2021 / 0015  
Replacing version dated / version: 13.11.2019 / 0014  
Valid from: 27.04.2021  
PDF print date: 28.04.2021  
Servolenkungsoel-Verlust Stop

dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EC European Community  
ECHA European Chemicals Agency  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
etc. et cetera  
EU European Union  
EVAL Ethylene-vinyl alcohol copolymer  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
IUPAC International Union for Pure Applied Chemistry  
LC50 Lethal Concentration to 50 % of a test population  
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.