

Page 1 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# **1.1 Product identifier**

# **Special Tec AA 5W-30**

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

അ

Sector of use [SU]: SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC17 - Hydraulic fluids PC24 - Lubricants, greases, release products Process category [PROC]: PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC20 - Use of functional fluids in small devices Article Categories [AC]: AC99 - Not required. Environmental Release Category [ERC]: ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 7 - Use of functional fluid at industrial site ERC 9a - Widespread use of functional fluid (indoor) ERC 9b - Widespread use of functional fluid (outdoor) Life cycle stages (LCS): LCS F - Formulation or re-packing LCS IS - Use at industrial sites LCS PW - Widespread use by professional workers LCS C - Consumer use Technical functions (TF): Lubricating agent Uses advised against: No information available at present.

### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

Emergency information services / official advisory body:



Page 2 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

# 2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Alkyl alcohol triester with boric acid. May produce an allergic reaction. EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

#### n.a. 3.2 Mixtures

Distillates (petroleum), hydrotreated heavy paraffinic		
Registration number (REACH)	01-2119484627-25-XXXX	
Index	649-467-00-8	
EINECS, ELINCS, NLP	265-157-1	
CAS	64742-54-7	
content %	20-30	
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304	
Baseoil - unspecified *		
Registration number (REACH)		
Index		
EINECS, ELINCS, NLP		
CAS		
content %	1-<10	
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304	
Bis(nonylphenyl)amine		
Registration number (REACH)	01-2119488911-28-XXXX	
Index		
EINECS, ELINCS, NLP	253-249-4	
CAS	36878-20-3	
content %	1-<5	
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 4, H413	

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

 \* The contained mineral oil can be described by one or more of the following numbers:

 EINECS, ELINCS, NLP
 Registration number (REACH)
 Chemical name

 265-157-1
 01-2119484627-25-XXXX
 Distillates (petroleum), hydrotreated heavy paraffinic



Page 3 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

അ

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Sensitive individuals:

reddening of the skin

Allergic reaction

# 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

**SECTION 5: Firefighting measures** 

# 5.1 Extinguishing media

#### Suitable extinguishing media

CO2 Foam Dry extinguisher Water mist

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures



Page 4 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

Ensure sufficient supply of air. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

#### **6.2 Environmental precautions**

If leakage occurs, dam up.

ആ

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration. If accidental entry into drainage system occurs, inform responsible authorities.

# 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

# 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation. Avoid formation of oil mist. Avoid contact with eyes or skin. Do not carry cleaning cloths soaked in product in trouser pockets. Do not heat to temperatures close to flash point. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing. Under all circumstances prevent penetration into the soil. Store at room temperature. Store in a dry place.

#### 7.3 Specific end use(s)

No information available at present.

**SECTION 8: Exposure controls/personal protection** 

# 8.1 Control parameters

Chemical Name	Oil mist, mineral			Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, e	excluding metal	WEL-STEL:		
working fluids, ACGIH)				
Monitoring procedures:	-	Draeger - Oil Mist 1/a (67 33 031)		
BMGV:			Other information:	

Distillates (petroleum), hydro	otreated heavy paraffinic					
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - oral (animal		PNEC	9,33	mg/kg	
	feed)					
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h



Page 5 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

ആ

Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3	8h

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,01	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - sediment, freshwater		PNEC	132000	mg/kg dw	
	Environment - sediment, marine		PNEC	13200	mg/kg dw	
	Environment - soil		DNEL	263000	mg/kg dw	
	Environment - periodic release		PNEC	1	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,31	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,09	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,31	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,62	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,37	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

# 8.2 Exposure controls

# 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.



Page 6 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

Eye/face protection:

ആ

Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection: Protective gloves, oil resistant (EN 374). If applicable Protective nitrile gloves (EN 374). Protective gloves made of polyvinyl alcohol (EN 374). Protective Viton® / fluoroelastomer gloves (EN 374). Minimum layer thickness in mm: >= 0,5 Permeation time (penetration time) in minutes: >= 480 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. With oil mist formation: Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

# 8.2.3 Environmental exposure controls

No information available at present.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Dhyeigel state:	Liquid
Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	220 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,850 g/cm3
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined



Page 7 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

Auto-ignition temperature: Decomposition temperature: Viscosity: Viscosity: Explosive properties: Oxidising properties:

#### 9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content: Not determined Not determined 60,0 mm2/s (40°C) 10,0 mm2/s (100°C) Product is not explosive. No

Not determined Not determined Not determined Not determined

# **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

# 10.3 Possibility of hazardous reactions

#### No dangerous reactions are known. **10.4 Conditions to avoid**

Strong heat

#### **10.5** Incompatible materials

Avoid contact with strong oxidizing agents. Avoid contact with strong alkalis. Avoid contact with strong acids.

#### **10.6 Hazardous decomposition products**

No decomposition when used as directed.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Distillates (petroleum), hydrotreated heavy paraffinic								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	Analogous conclusion		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion		



Page 8 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

œ.

Toxicity / effect		Value	Unit	Organism	Test method	Notes
Baseoil - unspecified						
	1					CONCIUSION
repeated exposure (STOT-RE), inhalat.:						Analogous conclusion
Specific target organ toxicity -	NOAEL	0,22	mg/l	Rat		Dust, Mist,
repeated exposure (STOT-RE), dermal:					Dose Dermal Toxicity - 90-Day)	conclusion
oral: Specific target organ toxicity -	NOAEL	1000	mg/kg	Rabbit	Toxicity Study in Rodents) OECD 410 (Repeated	Analogous
Specific target organ toxicity - repeated exposure (STOT-RE),	LOAEL	125	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral	Analogous conclusion
Aspiration hazard:						Yes
Developmental toxicity):					Developmental Toxicity Study)	Analogous conclusion
Reproductive toxicity				Rat	Test) OECD 414 (Prenatal	Negative,
					(Reproduction/Developm ental Toxicity Screening	Analogous conclusion
Reproductive toxicity:				Rat	OECD 421	conclusion Negative,
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous
					Micronucleus Test)	conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte	Negative, Analogous
					Mammalian Cell Gene Mutation Test)	Analogous conclusion
Germ cell mutagenicity:				Mouse	Aberration Test) OECD 476 (In Vitro	Negative,
					Mammalian Chromosome	Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative,
				typhimurium	Reverse Mutation Test)	Analogous conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	conclusion Negative,
sensitisation:					Sensitisation)	contact), Analogous
Respiratory or skin				Guinea pig	OECD 406 (Skin	conclusion No (skin
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous
					Dermal Irritation/Corrosion)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute	Aerosol Not irritant,

Baseon - unspecified						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Respiratory or skin						Not sensitizising
sensitisation:						
Aspiration hazard:						Yes

Foxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion



Page 9 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

œ)

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion
Germ cell mutagenicity:				Mouse	OECD 478 (Genetic	Negative,
					Toxicology - Rodent	Analogous
					dominant Lethal Test)	conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Reproductive toxicity	NOAEL	150	mg/kg	Rat	OECD 414 (Prenatal	Negative
(Developmental toxicity):			bw/d		Developmental Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	<100	mg/kg	Rat	OECD 408 (Repeated	
repeated exposure (STOT-RE),			bw/d		Dose 90-Day Oral	
oral:					Toxicity Study in	
					Rodents)	

# **SECTION 12: Ecological information**

Special Tec AA 5W-30 Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	Lindpoint	Time	Value	Unit	Organisin	rest method	n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							DOC-elimination degree(complex ng organic substance)>= 80%/28d: No

Distillates (petroleum), hydrotreated heavy paraffinic							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
12.2. Persistence and		28d	31	%	activated sludge	OECD 301 F	Readily
degradability:						(Ready	biodegradable,
						Biodegradability -	Analogous
						Manometric	conclusion
						Respirometry Test)	
12.3. Bioaccumulative	Log Pow		3,9-6				High
potential:							
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	Analogous
					mykiss	Acute Toxicity	conclusion
						Test)	



B Page 10 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	QSAR	Analogous conclusion
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
Other information:	AOX		0	%		,	

Baseoil - unspecified							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus quadricauda		
12.2. Persistence and degradability:		28d	31	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	NOEC/NOEL	72h	>10	mg/l	Desmodesmus		Analogous
					subspicatus		conclusion
12.2. Persistence and		28d	24	%		OECD 301 C	Not readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Modified MITI	
						Test (I))	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish,	Analogous
						Acute Toxicity	conclusion
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
	5050					Test)	
12.1. Toxicity to algae:	EC50	72h	600	mg/l	Pseudokirchneriell	OECD 201 (Alga,	Analogous
					a subcapitata	Growth Inhibition	conclusion
		0.0 1	-			Test)	
12.2. Persistence and		28d	1	%	activated sludge	OECD 301 B	Not readily
degradability:						(Ready	biodegradable,
						Biodegradability -	Analogous
						Co2 Evolution	conclusion
	Las Davi		. 7.0			Test)	Concentration in
12.3. Bioaccumulative	Log Pow		>7,6				Concentration in
potential:							organisms
12.3. Bioaccumulative	BCF		1730				possible.
potential:			1/30				High



Page 11 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

# **SECTION 13: Disposal considerations**

# **13.1 Waste treatment methods**

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

ആ

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Observe regulations for disposal of old oil/waste. E.g. suitable incineration plant.

# For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

# **SECTION 14: Transport information**

General statements 14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	
Unless specified otherwise, general measures for safe transport must b	e followed.
14.7. Transport in bulk according to Annex II of M	IARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.



Page 12 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

0,12 %

#### **15.2 Chemical safety assessment** A chemical safety assessment is not provided for mixtures.

**SECTION 16: Other information** 

Revised sections:

അ

1

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic

### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) The International Bromine Council BSEF body weight bw CAS **Chemical Abstracts Service** Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dry weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g. ΕČ European Community ECHA European Chemicals Agency European Economic Community EEC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN European Norms United States Environmental Protection Agency (United States of America) EPA etc. et cetera FU European Union



ആ Page 13 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.11.2020 / 0005 Replacing version dated / version: 29.07.2019 / 0004 Valid from: 25.11.2020 PDF print date: 12.03.2021 Special Tec AA 5W-30 EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential IARC International Agency for Research on Cancer International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code incl. including, inclusive IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry Lethal Concentration to 50 % of a test population LC50 Lethal Dose to 50% of a test population (Median Lethal Dose) LD50 LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable not available n.av. n.c. not checked no data available n.d.a. OECD Organisation for Economic Co-operation and Development organic org. PBT persistent, bioaccumulative and toxic Polyethylene PF PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

 $\textcircled$  by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.