

Fuel Protect

Description

Ash-free, self-mixing combination of active agents according to the latest additive, fuel and engine technology. Specially developed to satisfy the demands and operating conditions of today's engines. Prevents corrosion problems in the fuel system and thus prevents operational malfunctions.

Properties

- disperses water in the fuel
- keeps the fuel system clean
- prevents the negative effects of water in the fuel tank
- outstanding corrosion protection
- prevents sludge formation
- tested for turbochargers and catalytic converters

Technical data

Base	Additive, spezielle Trägerflüssigkeit / additives, special carrier fluid
Color / appearance	gelblich, klar / yellowish, clear
Density at 15 °C	0,800 g/ml
Refractive index at 20 °C	1,367
Form	flüssig / liquid
Viscosity at 40 °C	<7 mm ² /s
Odor	charakteristisch / characteristic

Areas of application

For all gasoline engines, specifically when used with fuels slightly contaminated with water.

Application

Add to fuel whenever filling up. 300 ml sufficient for 60 l fuel.



Available pack sizes

300 ml Can sheet metal	2530
	GB-ARAB-F
300 ml Can sheet metal	2811
	DK/N-S-FIN
300 ml Can sheet metal	2955
	GB-GR-I
300 ml Can sheet metal	8356
	D-E-P
300 ml Can sheet metal	21350
	D-GB-CN
5 l Canister plastic	2855
	D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.