

## Top Tec ATF 1400

### Description

High performance automatic transmission fluid of the new generation based on synthetic technology. It was developed specifically for use in CVTs with thrust link belt or a gear chain made of steel. The basis of modern base oils and select additives offer the best possible anti-froth protection, which is necessary for CVTs. It also features a very good stability against aging and oxidation. Top Tec ATF 1400 is tried and tested, most notably in the Mercedes-Benz A-Class and B-Class Autotronic transmissions and in continuously variable automatic transmissions (Multitronic) in Audi vehicles.

### Properties

- outstanding friction characteristics
- very good low-temperature properties
- excellent wear resistance
- prevents foam formation
- outstanding resistance to oxidation
- excellent corrosion protection
- excellent viscosity/temperature properties
- extremely stable to aging

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:**

Dodge CVTF+4 • Dodge NS-2 • Ford CVT23 • Ford CVT30 • Ford Mercon C • GM/Saturn DEX-CVT • Honda HCF2 • Honda HMMF • Hyundai SP-CVT 1 • Jeep CVTF+4 • Jeep NS-2 • Kia SP-CVT 1 • MB 236.20 • Mini Cooper (EZL 799) • Mitsubishi CVTF-J1 • Mitsubishi CVTF-J4 • Nissan CVT NS-2 Fluid • Nissan NS-3 CVT Fluid • Subaru E-CVT • Subaru High Torque CVTF • Subaru Lineartronic CV-30 • Subaru Lineartronic CVTF • Subaru Lineartronic CVTF II • Subaru NS-2 • Suzuki CVT Green1 • Suzuki CVT Green2 • Suzuki NS-2 • Suzuki TC • Toyota CVTF FE • Toyota TC • VW G 052 180 • VW G 052 516

### Technical data

Density at 15 °C	0,855 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	32,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	7,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40°C (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	194 DIN ISO 2909



### Technical data

Flash point	200 °C DIN ISO 2592
Pour point	-45 °C DIN ISO 3016
Color number (ASTM)	L 2,0 DIN ISO 2049

### Areas of application

For the new generation of CVTs with thrust link belt or a gear chain made of steel.

### Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

### Available pack sizes

1 l Can plastic	3662 D-GB-I-E-P
1 l Can plastic	3669 D-NL-F-GR-ARAB
1 l Can plastic	21257 ALGERIEN-GB-ARAB-F
20 l Canister plastic	3692 D-GB-I-E-P
60 l Drum sheet metal	20614 D-GB
205 l Drum sheet metal	3661 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**