

Product information

Catalytic-System Clean

PI 11/24/04/2019



Description

Protects the catalytic converter from clogging with soot. Cleans the injection system and the combustion chamber. The combustion improver works directly, which leads to an immediate, measurable reduction of the pollutants. Clean engines use less fuel and emit less CO₂. Prevents corrosion in the fuel system. Tested for use with turbochargers and catalytic converters.

Properties

- protects the catalytic converter from clogging with soot
- guarantees optimum combustion
- cleans the mixture preparation system as well as the intake valves and the combustion chamber
- prevents corrosion in the fuel system
- has a lasting effect
- guarantees low fuel consumption
- improves combustion
- immediate, measurable reduction of pollutants
- tested for turbochargers and catalytic converters

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellgelb, klar / light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	>61 °C
Pour point	-45 °C
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 40 °C	<7 mm ² /s
Density at 15 °C	0,765 g/cm ³

Areas of application

Suitable for all gasoline engines with a catalytic converter.

Application

Add to the fuel as a preventative measure. 300 ml is sufficient for up to 70 liters of fuel. Can be added at any time because mixing takes place automatically. Effect remains for up to 2,000 km.



Comment

Deposits in the catalytic converter based on manganese oxide cannot be removed.

Available pack sizes

300 ml Can sheet metal 7110
GB-ARAB-F

Our information is based on thorough research and may be considered reliable, although not legally binding.