## **Product information**

# **Engine Flush Plus**



#### **Description**

Engine Flush Plus is a specially formulated combination of additives and carrier fluid. In combination with the carrier fluid, the highly effective detergent and dispersant additives dissolve sludge and lacquer formers. All types of oil-soluble and oilinsoluble residues are brought into suspension and removed during the next oil change. An engine which has been cleaned of deposits and contamination and which is then filled with fresh oil not contaminated with old impurities can develop its full performance characteristics.



minutes. Then change the oil and the filter. Engine Flush Plus is compatible with all commercially available motor oils.

## **Properties**

- optimal engine performance
- highly economical
- does not attack common sealing materials
- gentle cleaning
- rapid cleaning
- tested for particulate filters and catalytic converters
- simple to use without disassembly
- minimizes wear
- tested for turbocharger

## **Technical data**

Color / appearance gelb, braun / yellow,

brown

Base Additiv, Trägerflüssigkeit

/ additive, carrier liquid

Flash point 63 °C

**DIN ISO 2592** 

Pour point -45 °C

**DIN ISO 3016** 

Form flüssig / liquid

Viscosity at 40 °C <7 mm<sup>2</sup>/s

Odor charakteristisch /

characteristic

### Available pack sizes

300 ml Can sheet metal 2657

D-E-P

300 ml Can sheet metal 8374

GB-ARAB-F

300 ml Can sheet metal 2784 GB-AUS

----

300 ml Can sheet metal 7142

ALGERIEN-GB-ARAB-F

300 ml Can sheet metal 20871

JP

300 ml Can sheet metal 21501

F-D

300 ml Can sheet metal 20818

D-GB-CN

Our information is based on thorough research and may be considered reliable, although not legally binding.

#### Areas of application

Cleaning and flushing out the oil circuits of gasoline and diesel engines. The use of Engine Flush Plus is dependent on the degree of contamination of the oil circuit. Can be safely used in vehicles with timing belt running in oil.

Not suitable for use on motorbikes with wet clutches.

#### **Application**

One 300 ml can is sufficient for up to 6 liters of oil. Add Engine Flush Plus to the motor oil at running temperature before changing the oil. After adding the product, allow the engine to idle for approx. 10