

Coolant Ready Mix RAF 11



Description

Ready-to-use mixture based on ethylene glycol. The antifreeze contains no amines, nitrites or phosphates and offers ideal protection from frost, rust and overheating through its special inhibitor formulation. This therefore provides reliable vehicle performance all year round.

Properties

- prevents operational malfunctions
- contains no amines, nitrites or phosphates
- ready for use
- outstanding corrosion protection
- provides outstanding protection against overheating
- prevents the cooling system from freezing up
- for extended change intervals (note manufacturer's instructions)

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Alfa Romeo 9.55523 • Behr • BMW GS 94000 • Chrysler MS-7170 • CUMMINS 85T8-2 • Deutz DQC CA-14 • Fiat 9.55523 • Iveco-Standard 18-1830 • JI Case JIC-501 • Lada/Avtovaz TTM VAZ 1.97.717-97 • Lancia 9.55523 • MTU MTL 5048 • Opel/GM GME L 46014 • Perkins • Saturn • Toyota Motor Corporation • Vauxhall GMEL1301 • Volvo Cars 128 6083 / 002 • Volvo Construction • Volvo Trucks

Technical data

Frost and overheating protection	-20 bis +104 / -20 to +104 °C
Base	Ethylenglykol mit Inhibitoren / ethylene glycol with inhibitors
Density at 20 °C	1,05 g/cm ³
Color / appearance	blau / blue
Flash point	k.D.v.
Shelf life in original sealed container	60 months

Areas of application

Suitable for all cooling systems and engines (including aluminium engines) in passenger vehicles, commercial motor vehicles, buses, agricultural machinery and stationary engines/machines where coolant system protection of this quality is required.

Application

Clean the coolant system with Radiator Cleaner (part no. 3320). Empty the coolant system, rinse thoroughly with water and fill with Coolant Ready Mix RAF11. Disposal is made according to the local regulations. The change intervals vary according to the manufacturer's instructions. Coolant Ready Mix RAF11 is mixable and compatible with radiator antifreeze containing silicates according to VW standard G11 – TL 774-C (LIQUI MOLY Radiator Antifreeze RAF11) or original silicate-free radiator antifreeze according to VW standard TL 774-D/F (LIQUI MOLY Radiator Antifreeze RAF12 Plus or LIQUI MOLY Coolant Ready Mix RAF12 Plus).

Available pack sizes

1 l Bottle plastic	20660
	D-GB-I-E-P
5 l Canister plastic	8809
	D-GB-I-E-P
20 l Canister plastic	8822
	D-GB
200 l Drum sheet metal	8823
	D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.