

## Marine Fully Synthetic 2T Motor Oil

### Description

Fully synthetic high-performance motor oil for 2-stroke outboard engines which biodegrades rapidly (CEC L-33-T-82 Test: 80 % in 21 days). Top quality basic oils and specially formulated additives provide for excellent lubrication, superb reliability and outstanding protection against wear and corrosion. Optimum engine cleanliness. No uncontrolled ignition, low-fuming combustion. With TC-W3-level performance.

### Properties

- optimum lubrication under all operating conditions
- prevents residues generated by combustion process
- biologically degradable
- high wear resistance
- burns ash-free
- prevents spontaneous ignition
- outstanding corrosion protection

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:**

NMMA TC-W3

### Technical data

Density at 15 °C	0,935 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	49 mm <sup>2</sup> /s DIN 51757
Viscosity at 100 °C	8,3 mm <sup>2</sup> /s DIN 51562
Viscosity index	145 DIN ISO 2909
Pour point	-45 °C DIN ISO 3016
Flash point	250 °C DIN ISO 2592
Biodegradability after 21 days	CEC L-33-T-82 CEC L-33-T-82 > 80 %
Color number (ASTM)	L 6,5 DIN ISO 2049

### Areas of application

For air and water-cooled 2-stroke marine engines with separate and premix lubrication systems. An outstanding product formulated for high-performance engines. Biodegradable (CEC L-33-T-82 Test: 80 % in 21 days)



### Application

Use as normal for two-stroke oils for mixture and separate lubrication systems. Keep to the mixing ratios stipulated by the relevant engine manufacturer.

### Available pack sizes

1 l Canister plastic	25021
	BOOKLET

**Our information is based on thorough research and may be considered reliable, although not legally binding.**