

Top Tec ATF 1100

Description

Synthetic technology automatic transmission oil with high performance reserves. Provides high thermal stability, ensuring ideal aging resistance. Excellent wear protection, favorable friction behavior, high safety reserves through modern additive technology, and with improved formula for long transmission life. Compatible with all sealing materials.

Properties

- excellent viscosity/temperature properties
- highest thermal stability
- outstanding friction characteristics
- minimizes wear
- high chemical resistance
- optimum stability to aging
- very good low-temperature properties
- excellent corrosion protection

Specifications and approvals:

Allison C4 • Dexron III G • Dexron III H • Dexron TASA (Typ A/Suffix A) • Ford Mercon • MAN 339 Typ L1 • MAN 339 Typ V1 • MAN 339 Typ Z1 • MB-Approval 236.1 • Voith H55.6335.XX (G 607) • ZF TE-ML 03D • ZF TE-ML 04D • ZF TE-ML 14A • ZF TE-ML 17C • ZF approval number ZF004926

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Allison TES 389 • Caterpillar TO-2 • Ford ESP-M2C 166-H • MB 236.6 • Volvo 97341 • ZF TE-ML 02F • ZF TE-ML 09 • ZF TE-ML 11A • ZF TE-ML 11B • ZF TE-ML 14B

Technical data

Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	36,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	7,5 mm ² /s ASTM D 7042-04
Viscosity at -40°C (Brook-field)	<= 20000 mPas ASTM D 2983-09
Viscosity index	180 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592



Technical data

Sulfate ash	0,10 g/100g DIN 51575
Shear stability, viscosity at 100 °C after 100 h	5,4 mm ² /s DIN 51350-06-KRL/C
Color / appearance	rot

Areas of application

For automatic transmissions, manual transmissions, power steering systems, hydraulic systems and auxiliary drives both in passenger vehicles and commercial vehicles as well as in industrial applications. Use according to the prescribed specifications from the unit or vehicle manufacturer.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Top Tec ATF 1100 can also be used for refilling systems in which traditional ATF oils are used. Optimum effectiveness, however, is only possible when the product is used on its own (i.e. no mixing).

Available pack sizes

500 ml Can plastic	3650 D-GB-I-E-P
1 l Can plastic	3651 D-GB-I-E-P
1 l Can plastic	3668 D-NL-F-GR-ARAB
1 l Can plastic	20467 D-PL-H-RO-TR
1 l Can plastic	21238 ALGERIEN-GB-ARAB-F
5 l Canister plastic	3652 D-GB-I-E-P
20 l Canister plastic	3653 D-GB-I-E-P
60 l Drum sheet metal	3654 D-GB

Product information

PI 41/25/08/2020



Top Tec ATF 1100

Available pack sizes

205 l Drum sheet metal 3655
D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.