

Motorbike Gear Oil (GL4) 80W-90 Scooter

Description

High-performance, high-pressure gear oil manufactured from carefully selected base oils and multifunctional additives. The oil can therefore be used in a wide range of drives and transmissions.

Properties

- does not attack common sealing materials
- excellent resistance to aging
- minimizes wear
- high pressure-absorption capability
- reduces running noise
- excellent viscosity/temperature properties

Specifications and approvals:

API GL4 • MIL-L 2105

Technical data

SAE class (gear oils)	80W-90 SAE J306
Density at 15 °C	0,895 g/cm ³ DIN 51757
Viscosity at 40 °C	143 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,5 mm ² /s ASTM D 7042-04
Viscosity at -26°C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	100 DIN ISO 2909
Pour point	-30 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Color number (ASTM)	L3,0 DIN ISO 2049

Areas of application

For transmissions and final drives with normal to high loading.

Application

During selection, keep to the viscosity class stipulated by the transmission manufacturer. Can be mixed with all branded gear oils. Fully effective only when used alone.



Available pack sizes

150 ml Tube plastic	1680 D-GB-I-E-P
150 ml Tube plastic	5929 D-F-I-GR

Our information is based on thorough research and may be considered reliable, although not legally binding.