

Product information

Super Leichtlauf 10W-40

PI 44/15/06/2021



Description

Low-friction motor oil based on synthetic technology. For the high requirements of modern, high-performance gasoline and diesel engines without maintenance interval extension. Saves fuel, provides optimum protection against wear and has a beneficial effect on sealing materials and thus on the leaktightness of engines. Therefore highly suitable for year-round use in vehicles with mileages of over 100,000 km.

Properties

- instant lubrication after cold start
- outstanding engine cleanliness
- miscible with all commercially available motor oils
- regenerates seals
- high shear stability
- especially suitable for vehicles with mileages over 100,000 km
- high lubrication reliability
- saves fuel and reduces pollutant emissions
- maintains seals
- smooth engine running
- excellent wear protection
- optimum stability to aging
- tested for turbochargers and catalytic converters

Specifications and approvals:

ACEA A3 • ACEA B4 • API SN • MB-Approval 229.3 • VW 501 01 • VW 505 00

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Fiat 9.55535-D2 • Fiat 9.55535-G2 • MB 229.1 • Peugeot Citroen (PSA) B71 2300 • Renault RN 0700 • Renault RN 0710

Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,870 g/cm ³ DIN 51757
Viscosity at 40 °C	95,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,0 mm ² /s ASTM D 7042-04
Viscosity at -30°C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25°C (CCS)	≤ 7000 mPas ASTM D5293

Technical data

Viscosity index	150 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	12,0 % CEC-L-40-A-93
Flash point	232 °C DIN ISO 2592
Total base number	10,8 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	2,5 DIN ISO 2049

Areas of application

Ideal for vehicles with mileages of over 100,000 km and for modern gasoline, diesel and turbocharged engines.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used un-mixed.

Available pack sizes

1 l Canister plastic	9503 BOOKLET
1 l Canister plastic	21236 ALGERIEN-GB-ARAB-F
1 l Canister plastic	21106 D-GB-CN
4 l Canister plastic	9504 BOOKLET
4 l Canister plastic	20670 ALGERIEN-GB-ARAB-F

Product information

Super Leichtlauf 10W-40

PI 44/15/06/2021



Available pack sizes

4 l Canister plastic	20698 D-GB-CN
5 l Canister plastic	9505 BOOKLET
5 l Canister plastic	20671 ALGERIEN-GB-ARAB-F
20 l Canister plastic	1304 D-GB-I-E-P
60 l Drum sheet metal	1302 D-GB
205 l Drum sheet metal	1303 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.